

PRESSURE SET SIMPLE HORIZONTAL

FEATURES AND TECHNICAL SPECIFICATIONS

- Includes check valve and manual reset button
- Includes a system that prevents dry running integrated into the electronic pressure controller itself.
- Voltage, run/fault and pressure gauge indicator light
- Prevent water hammer
- Do not require regulation, air pre-charge or maintenance.
- Pumps suitable for treating clean water
- Single-phase supply voltage 1 x 230 V x 50 Hz
- Starting pressure at 1.5 Bar



PRESSURE GROUP HYDROMATIC SERIES

Compact horizontal single pressure booster group with constant pressure and HYDROMATIC pressure controller integrated in the horizontal pump.

Includes mains connection cable (2.5m) with SCHUKO type plug.

CODE	MODEL	kW	FLOW (m ³ /h)*						
			0,5	1	1,5	2	2,5	3	3,5
BO-3216-02	GPH HX2-40 + HYDROMATIC	0,55	36	34,5	33	29	25	20,5	16
BO-3216-04	GPH HX2-50 + HYDROMATIC	0,55	45,5	43	40	36	31,5	26,5	20,5
BO-3216-06	GPH HX2-60 + HYDROMATIC	0,75	53,5	51	48	44	39	32	24

CODE	MODEL	kW	FLOW (m ³ /h)*						
			1	2	3	4	5	6	7
BO-3216-10	GPH HX4-40+ HYDROMATIC	0,75	37,5	36	34	31	27	23	19
BO-3216-12	GPH HX4-50 + HYDROMATIC	1,1	47	45	42,5	39	34	29	23
BO-3216-14	GPH HX4-60 + HYDROMATIC	1,1	56	54	51	47	41,5	35,5	28

*Flow rates and power in kW are per pump per unit.

FT-EN-HYDROMATIC-BO-3216-XX-FL25V01