

DOUBLE VERTICAL GROUPS

INTEGRATED DRIVE SERIES IN THE PANEL



Compact constant pressure systems with variable speed drive integrated into the electrical panel.

- Three-phase power equipment mounted on a galvanized base or stainless steel structure
- Includes sectioning keys, non-return valve, 0-10 Bar glycerin pressure gauge.
- Boiler tank not included.
- MANUAL - or - AUTOMATIC selector on each pump
- On request, panel to operate with inverter or pressure switches using manual selector.
- Power and thermal pilots for each pump.
- Low water warning light.
- 0-10 bar pressure transducer
- Forced ventilation

CODE	MODEL	kW	FLOW (m ³ /h)*								
			0	2,5	3	4	5	6	7	8	8,5
BO-3230-06	GPDV VX-5-7-III	1,1	52	49,5	48,5	46	42,5	38,5	31,5	24,5	21
BO-3230-08	GPDV VX-5-10-III	1,5	74,5	71	70	66	62	55	46	35	30

CODE	MODEL	kW	FLOW (m ³ /h)*						
			0	5	6	8	10	12	14
BO-3230-14	GPDV VX-10-6-III	2,2	67	63	62	58	52	44	34
BO-3230-16	GPDV VX-10-8-III	3	90	85	84	79	71	60	46

CODE	MODEL	kW	FLOW (m ³ /h)*									
			0	8	10	12	14	15	16	18	20	22
BO-3230-32	GPDV VX-15-4-III	4	54	50,5	50	49	47,5	47	46	43	39	34
											28,5	

CODE	MODEL	kW	FLOW (m ³ /h)*										
			0	10	12	14	16	18	20	22	24	26	28
BO-3230-42	GPDV VX-20-4-III	5,5	55,5	52,5	51	50	49	48,5	47	45	41,5	37	33
												31,5	

*Flow rates and power in kW are unitary per pump

FT-EN-GPDV-BO-3230-XX-FL25V01