




GPBEV1 35-5T SIMPLE



GPBEV1 35-5T DUPLEX



GPBEV1 35-5T TRIPLE



GPBEV2 DUPLEX

GPBEV PRESSURE GROUPS

ALL PRESSURE GROUPS INCLUDE:

- 1 unit. Discharge manifold made of AISI 304 stainless steel.
- Check valves (one unit per pump)
- Shut-off valves (one unit per pump)
- 1 pc. 10 bar glycerin pressure gauge.
- 1 unit. Hydrosphere accumulator with a capacity of 24L and a maximum pressure of 8 bar
- Variable speed drives Model PDH30 3T (one unit per pump)
- 1 unit. Pressure transducer with a measuring range of 0-10 bar, 24V power supply and 4-20 mA analog signal output
- 1 unit. Omega type bench made of folded iron with a thickness of 3 mm, with reinforcement up to 200 kg and painted in RAL 9001
- 1 unit. Protective frame support made from a square iron profile and painted in RAL 9001.
- Suction manifold NOT included.

GPBEV1 Three-phase variable speed clean water pressure groups, equipped with multi-stage centrifugal vertical electric pumps and hydrosphere accumulator.

Simplex : 1 pc. Multistage centrifugal vertical electric pump with pack tea fully hydraulic tea in AISI 304 stainless steel

Duplex : 2 units of multistage centrifugal vertical electric pumps with pack tea fully hydraulic tea in AISI 304 stainless steel.

Triplex 3 units of multistage centrifugal vertical electric pumps with pack tea fully hydraulic tea in AISI 304 stainless steel

GPBEV2 Three-phase variable speed clean water pressure groups, equipped with multi-stage centrifugal vertical electric pumps with main pump rotation and hydrosphere accumulator.

Duplex : 2 units of multistage centrifugal vertical electric pumps with pack tea fully hydraulic tea in AISI 304 stainless steel.

Triplex 3 units of multistage centrifugal vertical electric pumps with pack tea fully hydraulic tea in AISI 304 stainless steel

CODE	MODEL	kW	FLOW (m³/h)*							
			0	5	7,5	10	13	15	20	25
GPBEV1										
BO-GPBEV1S35-5T	BEV1 35-5T SIMPLE	2,1	75	61	45	25				
BO-GPBEV1S55-4T	BEV1 55-4T SIMPLE	2,5	52	45	42	36	30	22		
BO-GPBEV1S55-6T	BEV1 55-6T SIMPLE	3,9	82	73	68	60	46	39		
BO-GPBEV1D35-4T	BEV1 35-4T DUPLEX	1,7	62	45	32	20	5			
BO-GPBEV1D35-5T	BEV1 35-5T DUPLEX	2,1	75	61	48	25				
BO-GPBEV1D35-6T	BEV1 35-6T DUPLEX	5	88	71	53	30				
BO-GPBEV1D55-4T	BEV1 55-4T DUPLEX	2,5	52	45	42	36	29	22		
BO-GPBEV1D55-6T	BEV1 55-6T DUPLEX	3,9	82	75	68	60	46	39		
BO-GPBEV1T35-5T	BEV1 35-5T TRIPLEX	2,1	75	61	43	23				
BO-GPBEV1T55-4T	BEV1 55-4T TRIPLEX	2,5	52	45	42	36	29	22		
BO-GPBEV1T55-6T	BEV1 55-6T TRIPLEX	3,9	82	71	65	59	48	38		
GPBEV2										
BO-GPBEV2D15-5T	BEV2 15-5T DUPLEX	4	68	68	66	63	60	58	48	
BO-GPBEV2D20-4T	BEV2 20-4T DUPLEX	5,5	55	55	53	52	51	50	43	39
BO-GPBEV2T15-5T	BEV2 15-5T TRIPLEX	4	68	60	51	38				
BO-GPBEV2T20-4T	BEV2 20-4T TRIPLEX	5,5	55	50	40	32				

*The flow rates and po tea The kW indicated are unitary per pump

FT-EN-GPSV GPBEV-BO-GPBEVXXXX-XT-FL24V01