



NSX Pumps

FLOW PUMPS

Horizontal single-stage stainless steel pumps.

Horizontal single-stage stainless steel centrifugal pumps manufactured with laser welding and hydroforming. Resistant to slightly corrosive liquids. Its relevant features are its design, its light and manageable structure, its high efficiency and energy saving, its durability, its resistance to corrosion, its silent operation, etc.

CODE	MODEL	kW	FLOW (m³/h)*						
			5	10	15	20	25	30	35
BO-NSX6540-15	NSX 65-40-125/1.5	1.5	15.5	15.4	15	14.4	13	11.3	
BO-NSX6540-22	NSX 65-40-125/2.2	2.2	20	19.7	19.5	19	18	16.7	15.2
BO-NSX6540-30	NSX 65-40-125/3.0	3.0	25.7	25.3	25.1	24.8	24	22.3	23
			5	10	20	30	40	50	60
BO-NSX6540-40	NSX 65-50-125/4.0	4.0	24.2	24.2	23.6	22.6	20.7	18	14.8
BO-NSX6540-55	NSX 65-50-160/5.5	5.5	31.6	31.5	31	30	28	25	21.5

CODE	MODEL	kW	FLOW (m³/h)*									
			40	50	60	70	80	90	100	110	120	130
BO-NSX8565-55	NSX 80-65-125/5.5	5.5	19.3	18.7	18	17	15.5	14.8	13	11.4	9.7	
BO-NSX8565-92	NSX 80-65-125/9.2	9.2	28.1	27.8	27.3	26.6	25.7	24.3	23	21.5	20.1	18.3

CODE	MODEL	kW	FLOW (m³/h)*										
			1,2	2,4	3,6	4,8	6	7,2	8,4	9,6	12	15	18
BO-MN100-11S	MN100/1.1 mono	1.1		27.4	26.3	25	23.4	21.5	19.5	16.7			
BO-MN100-11T	MN100/1.1 three	1.1											
BO-MN250-22T	MN250/2.2 three	2.2					15.8	15.6	15.4	15	14.3	13	11.5

CODE	MODEL	kW	FLOW (m³/h)*							
			0	5	10	15	20	25	30	35
BO-MXC15-11T	MXC15/1.1 tri	1.1	15	14	14	13	12			
BO-MXC25-22T	MXC25/2.2 tri	2.2	16	16	15	15	14	14	13	13

CODE	MODEL	kW	FLOW (m³/hour)				
			0.3	1.2	1.8	2.4	2.7
BO-2202-04	JESX5 MONO	0.37	28	23	20	13	11.5
BO-2202-02	YESSX5 THREE	0.37	28	23	20	15	11.5

*The indicated flow rates are unitary per pump