



FLANGE  
Connection

## PULSE EMITTER WATER METER

### FLANGES

- Brass body
- Supplied without flanges
- They guarantee the highest degree of sensitivity, precision and resistance.
- Head made of very hard materials to offer maximum protection
- Suitable for cold water

| CODE       | CALIBER |        | CONNECTION | LENGTH (mm) | NOMINAL FLOW (m <sup>3</sup> /h) | MINIMUM FLOW (L/h) | Nº PULSES   |
|------------|---------|--------|------------|-------------|----------------------------------|--------------------|-------------|
|            | mm      | INCHES |            |             |                                  |                    |             |
| CO-0402-10 | 50      | 2"     | Bridles    | 170         | 15                               | 1200               | 1 imp/1000L |
| CO-0402-11 | 70      | 2 ½"   | Bridles    | 200         | 35                               | 2000               | 1 imp/1000L |
| CO-0402-12 | 80      | 3"     | Bridles    | 200         | 50                               | 2500               | 1 imp/1000L |
| CO-0402-13 | 100     | 4"     | Bridles    | 250         | 75                               | 3600               | 1 imp/1000L |
| CO-0402-17 | 125     | 5"     | Bridles    | 300         | 125                              | 4500               | 1 imp/1000L |
| CO-0402-18 | 150     | 6"     | Bridles    | 300         | 150                              | 5000               | 1 imp/1000L |

For other configurations in the number of pulses / L, consult our technical department.