

TWIN WS1.5TT DF NORYL

CLACK 1" ½ SOFTENER

Twin alternating softener for removing hardness using ion exchange resins.

Clack WS1.5TT DF Noryl volumetric valve for control of the two bottles, digital programmer and delayed, instantaneous or mixed downflow regeneration.

The valve made of Noryl improves resistance to chemicals and has a greater tolerance in saline or corrosive environments compared to metals. Its lower weight simplifies handling.

Permanently softened water, only one bottle in service, the second in regeneration phase or on stand-by.

- Its special design allows for optimal service flow rates (up to 12.3m³/h) and backwashes.
- GRP vessel reinforced in polyester
- Regeneration frequency from 1 to 28 days
- Turbine for controlling the volume of treated water
- Includes collector between bottles
- 1 1/2" Connection
- Loaded with food grade resin of high capacity with high performance
- Working pressure: 2.5 to 6 Bar
- Maximum temperature: 43°C
- Power supply: 230V-15Vdc 50/60 Hz

CODE	DIMENSIONS (mm)					
	D1	Hb	Hv	Ht	Dd	Hd
ED-3605-57	363	1674	281	1955	530	1000
ED-3605-58	413	1671	281	1952	600	1140
ED-3605-59	413	1671	281	1952	600	1140
ED-3605-60	491	1722	281	2003	600	1140
ED-3605-61	491	1722	281	2003	905	1140
ED-3605-62	555	1721	281	2002	905	1140
ED-3605-63	635	1918	281	2199	905	1140
ED-3605-65	635	1918	281	2199	1200	1320

CODE	RESIN LOADING (L)	WORKING FLOW RATE (m³/h)	SALT CONSUMP. (Kg)	SALT TANK (L)
ED-3605-57	2x100	4	20	300
ED-3605-58	2x125	5	25	300
ED-3605-59	2x140	5,6	28	500
ED-3605-60	2x170	6,8	34	500
ED-3605-61	2x200	8	40	500
ED-3605-62	2x225	9	45	500
ED-3605-63	2x300	12	60	500
ED-3605-64	2x350	12,3	70	1000

CODE	MODEL
AV-3002-22	Kit micro Clack 1" - 1 1/4" - 1 1/2"

FT-EN-DESCAL WS1.5TTDF NORYL-ED-3605-XX-FL24V01



The image could do not correspond to the model.

