



Does not include batteries

FLAT PROJECTOR

COLD-WARM WHITE LED

- Flat LED light manufactured in white ABS.
- Low power consumption.
- 100% waterproofing security thanks to Epoxy filling.
- Installation in concrete (for liner, optional support).
- Supplied with 2.5 meter cable.
- LED type SMD2835.
- Voltage: AC 12V / 50-60 Hz.

REMOTE CONTROL PROGRAMMING

- | | |
|---------------|---|
| 1. ON | 5. Compound Pattern Cool White-Warm White |
| 2. OFF | 6. / |
| 3. Warm white | 7. Decrease brightness |
| 4. Cool white | 8. Increase brightness |

1. This light is powered with 12V AC. It has to be connected to the transformer, never directly to the electric network directly.
2. The connection box must be at least 1.2m from the edge of the pool.
3. The installation plate should be placed in such a way that the upper part of the spotlight is at least 450mm below the water level of the pool.
4. The light must always be placed on flat surfaces. Screw the fixing plate with the four screws.
5. Connect the cables with their corresponding ones in the connection box and fill with epoxy glue.
6. Before testing the lamp for more than ten seconds, it must be immersed completely in water.

3

Different Colours

Warm Cold Compound

5

Brightness levels

20% 40% 60% 80% 100%

**POSSIBILITY TO SET THE SPOTLIGHT AT
3000K, 4000K AND 6400K**

PROJECTOR CONNECTION

Cable protector. If the interconnection of the cables is done below the water level, this connection must be made with a watertight joint or / and epoxy glue. Otherwise, moisture could enter the focus through the cable, voiding the warranty.



CODE	DESCRIPTION	FAMILY
HP-0205-90	Cable protector	A

CODE	MODEL	LUM.	POWER (W)	UNIT. BOX	FAM.
HP-0207-34	COLD-WARM White flat projector	1600	18	1	A
HP-0207-99	Optional support for liner pools				A