

HEAT PUMP
JETLINE SELECTION FI



FULL INVERTER TECHNOLOGY

Its Full Inverter technology allows you to vary the speed of its compressor and fan to adapt perfectly to demand, thus reducing energy consumption and sound pressure.

By design and large evaporation surface made of hydrophilic aluminium, the Jetline Selection Fi operates at a temperature of -7°C.

With the new Twisted Tech © heat exchanger technology with a twisted titanium coil, the pool temperature is even faster.

MAIN FEATURES

- **Full Inverter** Technology.
- Reversible.
- Automatic defrosting.
- **Twisted Tech©** titanium heat exchanger.
- Compatible with salt treatment.
- Pool heat pump warranties:
 - Compressor 5 years.
 - Titanium Coil 15 years (against corrosion).
 - Rest of components 3 years.

ACCESSORIES INCLUDED



Set of supports anti-vibration



Condensation drain pipe



Extension of the wired remote control (10 m)



Ø 50 mm 1'' ½ PVC connectors



Winter cover



CODE	MODEL	FAMILY
HP-8040-02	Reversible heat pump Jetline with wifi 75	B
HP-8040-04	Reversible heat pump Jetline with wifi 95	B
HP-8040-06	Reversible heat pump Jetline with wifi 125	B
HP-8040-08	Reversible heat pump Jetline with wifi 155	B
HP-8040-10	Reversible heat pump Jetline with wifi 210	B

* IT IS RECOMMENDED TO ALWAYS COVER THE POOL WHEN NOT IN USE.

	75	95	125	155	210
	HP-8040-02	HP-8040-04	HP-8040-06	HP-8040-08	HP-8040-10
	CAPACITY: AIR AT 26°C, WATER AT 26°C, HUMIDITY 80%				
Recommended pool volume (m³)	30 - 45	40 - 50	45 - 65	65 - 80	80 - 110
Max. rated power (kW)	7,1	9,5	11,9	15,3	20,1
Min. rated power (kW)	2,04	2,3	2,35	2,5	2,77
Consumption (kW)	1,15	1,51	1,92	2,51	3,24
COR	6.2 ~ 13.6	6.3 ~ 14	6.2 ~ 16.4	6.1 ~ 16.3	6.2 ~ 16.5
	CAPACITY: AIR AT 15°C, WATER AT 26°C, HUMIDITY 80%				
Max. rated power (kW)	5,4	6,7	8,7	10,9	14,6
Min. rated power (kW)	1,4	1,5	1,7	1,9	2,15
Consumption (kW)	1,15	1,49	1,89	2,37	3,17
COR	4.7 ~ 6.5	4.5 ~ 6.6	4.6 ~ 7.8	4.6 ~ 7.7	4.6 ~ 7.9
	GENERAL DATA				
Power supply	Mono 230V / 50Hz				
Heating temperature range	15°C / 40°C				
Operating range	-7°C / 43°C				
Max. power (kW)	1.38	1.83	2.62	2.9	4.2
Exchanger	Twisted Tech© Titanio				
Type of compressor	DC inverter compressor				
Brand of compressor	Mitsubishi				
Coolant	R32				
Water flow (m³/h)	2~4	3~4	4~6	5~7	7~9
Sound level 1m far away (dB)	37~50	37~51	38~52	40~54	41~55
Sound level 10m far away (dB)	19~29	19~30	21~31	23~34	23~35
Weight net/gross (Kg)	37,5 / 43,5		39,5 / 45,5		50,5 / 59
Measurement (mm)	886 x 404 x 778			969 x 404 x 778	1166 x 424 x 878
Packaging (mm)	824 x 334 x 656			907 x 334 x 656	1104 x 354 x 756
Function	Eco & Boost Inverter / Heating / Cooling				
Head losses (mCE)	0,9	1	1,1	1,1	1,2

