

COMPACT all-in-one reverse osmosis:

- QC1 cartridges
- Antibacterial NANOSILVER post-filter
- 75 GPD membrane
- WaterStop
- Tank
- All in one practical piece of furniture that doesn't take up space under the sink.

Kalys



- Nanosilver Technology**
This technology eliminates 99.9% of bacteria.
- Large flow of water**
Thanks to its 75 GDP membrane and its 3/8" TUBE.
- Large capacity tank**
3.2 gallon tank.
- Easy installation and maintenance**
Equipped with cartridges QC1 bayonet fittings that facilitate installation and maintenance.
- Safety System**
It incorporates the WATER STOP anti-leak system and, for equipment with a pump, also a reducer. depression.
- European Certificate of Conformity**

COMPACT DOMESTIC REVERSE OSMOSIS


Compact reverse osmosis system that produces pure water with reduced salt content.

The Kalys omosis incorporates exclusive QC1 bayonet cartridges that simplify and reduce installation and maintenance time.

This system is equipped with very reliable safety devices, including the WATER STOP leak detector and a pressure regulator in models that have a booster pump.


KALYS COMPACT REVERSE OSMOSIS

- PP filtration 5µm
- GAC carbon
- CTO Carbon Block
- 75 GPD Membrane encapsulated
- Antibacteria NANOSILVER Post-filter
- Booster pump option



SYSTEM MEASURES

CODE	DIMENSIONS (mm)			WEIGHT (Kg)	
	A	B	C	Net	Gross
RO-0238-01	250	430	420	10,50	11,50
RO-0238-03	250	430	420	13,50	14,50



PACKAGING AND TRANSPORTATION

CODE	DIMENSIONS (mm)			LOGISTICS (units)		
	A	B	C	Pallet	Cont. 20'	Cont. 40'
RO-0238-01	500	310	540	32	380	760
RO-0238-03	500	310	540	32	380	760



QC1 bayonet cartridges



- QC1 bayonet cartridges for easy installation and maintenance
- 100% coconut shell activated carbon
- High water flow: 3/8" TUBE
- 75 GPD Membrane encapsulated
- Antibacteria NANOSILVER Post-filter.
- 3.2 gallon storage tank
- Installation kit
- Includes New Look faucet
- 1/4" pressure reducer in model with booster pump
- WATER STOP 1/4" leak detector: accurate and proven system leak detection system that cuts off the water supply even with small leaks. Low installation cost and no requires electrical installation.
- Working pressure:
 - Equipment with pump: 1 to 3 Bar
 - Equipment without pump: 2.5 to 4.2 Bar
- Inlet temperature: 5 to 35 °C
- TDS Maximum input : 1.000 ppm
- Pump equipment:
 - Power supply: 220 – 24VDC
 - Booster pump LF-30LN

CODE	MODEL
CA-0222-02	QC1 PP sediment cartridge 5µm
CA-0222-04	QC1 GAC carbon cartridge
CA-0222-05	QC1 CTO carbon block cartridge
ME-0218-03	Membrane encapsulated 18x12 75GPD
OI-0205-18	Postfilter antibact. CTO 2"x10" NANOSILVER
CA-7014-12	QC1 cartridge kit
RO-0238-01	KALYS compact reverse osmosis
RO-0238-03	KALYS compact reverse osmosis + pump

FT-EN-RO KALYS-RO-0238-XX-FL25V01