



DOMESTIC REVERSE OSMOSIS DIRECT FLOW

Maximum performance and simplicity in a very small unit. Water quality and cartridge change indicators for extremely simple maintenance.



QUICK CONNECTION

Rotates and extracts filters and membrane. Safe, efficient and fast mechanics.



DIRECT FLOW

No tank required.



LED STATUS INDICATORS

Information on water quality and cartridge life.



HIGH EFFICIENCY

High performance technology that achieves maximum flow with less rejection.



CARTRIDGES AND MEMBRANE

original and exclusive



600 GPD

High performance to offer great flow.



SOUND WARNING

Leak and production cut indicator.



WATER QUALITY CONTROL

TDS Notice



AUTOMATIC MAINTENANCE NOTICE

Through LEDs and sound



QUICK AND EASY MAINTENANCE


Twist and pull out.

ECUS DIRECT FLOW REVERSE OSMOSIS

Filtering system containing:


- 1.- PP + CTO bayonet prefilter (PRE),
- 2.- Bayonet membrane 600 GPD (ME),
- 3.- Postfilter bayonet CTO (POST)

- Intuitive interface with LED warnings for prefilter, membrane and postfilter.
- Includes ECUS faucet
- Peak flow rate: 1,6 Lpm
- Membrane 600 GPD
- TDS Maximum input : 1.000 ppm
- High performance diaphragm booster pump
- Decorative front to cover access to cartridges
- Inlet pressure: 1 to 4 Bar
- Inlet temperature: 5 to 35 °C
- Power supply: 24Vdc.
- External power adapter: 100-240V 50/60Hz: 24Vdc



SYSTEM MEASURES

CODE	DIMENSIONS (mm)		
	A	B	C
RO-8001-01	136	433	455



PACKAGING AND TRANSPORTATION

CODE	DIMENSIONS (mm)			LOGISTICS
	A	B	C	
RO-8001-01	590	250	560	Pallet 24 Units.

**HIGH RANGE DIRECT FLOW
reverse osmosis:**

- 2 Cartridges
- 1 Membrane
- Easy and fast connection
- 600 GPD: high flow
- No tank
- It does not take up space under the sink.



CODE	MODEL
CA-6001-01	PP + CTO Prefilter
ME-5001-01	ECUS membrane 600 GPD
CA-6001-02	CTO Postfilter
RO-8001-01	ECUS Direct Flow Compact Reverse Osmosis

FT-EN-RO-FLUJO-DIRECTO-ECUS-RO-8001-01-FL24V01