

Clack®



WS2Ci UF NORYL

UPFLOW

CLACK 2" SOFTENER

Automatic bibloc water softener for removing hardness using ion exchange resins.

Clack WS2Ci UF Noryl volumetric valve, digital programmer and instantaneous, delayed or mixed upflow regeneration.


LOW SALT CONSUMPTION.

The valve made of Noryl improves resistance to chemicals and has a greater tolerance in saline or corrosive environments compared to metals. Its lower weight simplifies handling.

The image can do not correspond to the model.



2" Noryl shut-off valve



- GRP vessel reinforced in polyester
- Regeneration frequency from 1 to 28 days
- External turbine for controlling the volume of treated water
- 2" Connection
- Loaded with food grade resin of high capacity with high performance
- Working pressure: 2.5 to 6 Bar
- Maximum temperature: 43°C
- Power supply: 200~240V 50/60Hz 15Vdc

CODE	DIMENSIONS (mm)					
	Db	Hb	Hv	Ht	Dd	HD
UF-3206-58	413	1671	317	1988	620	1230
UF-3206-60	486	1722	317	2039	620	1230
UF-3206-62	550	1721	317	2038	905	1140
UF-3206-64	626	1915	317	2235	1200	1320
UF-3206-65	780	1836	317	2153	1200	1320
UF-3206-66	938	1856	317	2173	1510	1350

CODE	RESIN LOADING (L)	WORKING FLOW RATE (m³/h)	SALT CONSUMP. (Kg)	SALT TANK (L)
UF-3206-58	166	5,6	16.6	300
UF-3206-60	240	8,2	24	300
UF-3206-62	300	10,2	30	500
UF-3206-64	430	14,6	43	1000
UF-3206-65	700	20	70	1000
UF-3206-66	990	20	99	1500

CODE	MODEL
VA-3005-22	Noryl 2" shut-off valve

FT-EN-DESCAL WS2CLUF-UF-3206-XX-FL25V01