

TECHNICAL FEATURES

- **Intuitive interface** with LED displays for pre-filter, membrane and post-filter.
- **Includes Ecus tap**
- **Peak flow rate:** 1.6 Lpm (flow rate may vary depending on water pressure, temperature and salinity)
- **600 GPD** membrane
- **Maximum inlet TDS:** 1.000 ppm
- High performance diaphragm **booster pump**
- **Decorative front panel** to cover access to cartridges
- **Inlet pressure:** 1 to 4 Bar
- **Inlet temperature:** 5 to 35 °C
- **Power supply:** 24Vdc
- **External power adaptor:** 100-240V 50/60Hz: 24Vdc

FILTRATION PROCESS

PRE -> PP + CTO Bayonet pre-filter
(CA-6001-01)

ME -> 600 GPD Bayonet membrane
(ME-5001-01)

POST -> Bayonet CTO postfilter
(CA-6001-02)



MAXIMUM
EFFICIENCY
600 GPD
MINIMUM
SPACE



www.hidro-water.com



DISTRIBUTOR:



ULTRA-COMPACT
DIRECT FLOW
REVERSE OSMOSIS FOR DOMESTIC WATER



MAXIMUM FUNCTIONALITY VERY EASY MAINTENANCE

Maximum performance (600 GPD membrane), and simplicity in a very small unit. Water quality and cartridge change indicators for extremely easy maintenance.



COMPACT AND TANKLESS EQUIPMENT
Designed to take up very little space under the sink




**MAXIMUM FLOW 1,6 Lpm
WITH MINIMUM REJECTION 2:1**
2 LITRES PRODUCED
1 LITRE REJECTED
Efficiency and sustainability



SIMPLICITY
Pre-filtration, membrane and post-filtration in cartridges that can be removed with a simple click.



SMART EQUIPMENT
with LEDs and audible warnings that inform about water quality, cartridge change, leaks and production stoppages.



ECUS TAP
Included



THE FASTEST, EASIEST, MOST SUSTAINABLE OSMOSIS WATER



FAST CONNECTION
Rotates and removes filters and membrane with a single click.



DIRECT FLOW. No tank required. Water is osmosed and offered directly.



INDICATOR LEDS
Information on water quality and cartridge life.



HIGH EFFICIENCY 2:1 REJECTION
600 GPD membrane offering 2 litres of water per 1 litre of rejection.



CARTRIDGES AND MEMBRANES
Original and exclusive: Prefiltration PP + CTO (PRE), Membrane 600 GPD (ME), and PostFilter (POST).




600 GPD - FLOW RATE 1,6 Lpm
High performance for high flow. Fills your water glass in 12 seconds



SOUND WARNING
Leakage and outage indicator



WATER QUALITY CONTROL
TDS Notification



EQUIPMENT MEASURES

CODE	DIMENSIONS (mm)		
	A	B	C
RO-8001-01	136	443	455